

## QC STL PRO-4.8X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 408 Watts / Med: 225 Watts / Low: 73.9 Watts	
Air Flow	Hi: 4280 CFM / Med: 3500 CFM / Low: 2361 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3130 CFM / Med: 2560 CFM / Low: 1670 CFM	
dBA	Hi: 47.4 / Med: 43.2 / Low: 33.0	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1427 SQFT to 2140 SQFT	
Minimum Attic Clearance	36"	
# of Speeds	3	
Duct Diameter	18"	
Duct Length	9 feet	
Motor Head Diameter	18 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	5.71 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	75 lbs.	
Box Dimensions	36" x 22" x 40"	
In The Box	<ul style="list-style-type: none"> <li>-QC STL PRO-4.8X Motorhead</li> <li>-Removable Grille</li> <li>-Cut-out Template</li> <li>-Window Locks</li> </ul>	<ul style="list-style-type: none"> <li>-Damper Box</li> <li>-9 Foot Duct</li> <li>-Accessory Bag</li> <li>-Controls</li> </ul>



For more information, visit our website at:  
[www.HouseFanPros.com](http://www.HouseFanPros.com)

QC STL PRO-4.8X  
QuietCool Stealth Pro Line